

borg &
overström

ELITE



Offering added enhancement through refined styling, the B&O Elite boasts all the features and options of the Classic, plus other user benefits. These include a larger dispensing area, integral cup dispenser and the option of sparkling water, giving a distinctive edge to your corporate refreshment system.

PRESTIGIOUS POINT-OF-USE COOLER OF STURDY CONSTRUCTION

TOUCH-PANEL CONTROLS AND INTEGRAL CUP DISPENSER

AUTO-LIT DISPENSING AREA OF GENEROUS DIMENSIONS

AVAILABLE AS FLOOR STANDING OR COUNTER TOP

A CHOICE OF WATER OPTIONS, INCLUDING HOT, AMBIENT, COLD, DIRECT-CHILL AND SPARKLING



A Z U R E

borg & overström

ELITE



| MACHINE TYPE (see key) | ● | ● | ● | ● | ○ |
|-----------------------------------|---------|---------|---------|---------|---------|
| COOLING SYSTEM | | | | | |
| Thermostatic Control Regulated | ● | ● | ● | ● | ● |
| Ice Bank Direct Chill | - | - | ● | ● | ● |
| Stainless Steel Tank | ● | ● | - | - | - |
| HEATING SYSTEM | | | | | |
| Stainless Steel Tank | - | ● | - | ● | - |
| Tank Size (litres) | - | 2 | - | 2 | - |
| Easy change tank | - | ● | - | ● | - |
| COLOUR | | | | | |
| Silver | ● | ● | ● | ● | ● |
| Graphite | - | - | - | - | - |
| COUNTER TOP DIMENSIONS | | | | | |
| Model Number | CW728 | CW728H | DC728 | DC728H | - |
| Width (mm) | 325 | 325 | 325 | 325 | - |
| Depth (mm) | 380 | 380 | 380 | 380 | - |
| Height (mm) | 475 | 475 | 475 | 475 | - |
| FLOOR STANDING DIMENSIONS | | | | | |
| Model Number | CW798 | CW798H | DC798 | DC798H | DC798CS |
| Width (mm) | 325 | 325 | 325 | 325 | 325 |
| Depth (mm) | 365 | 365 | 365 | 365 | 365 |
| Height (mm) | 1060 | 1060 | 1060 | 1060 | 1060 |
| STORAGE BASE DIMENSIONS | | | | | |
| Internal Width (mm) | 320 | 320 | 320 | 320 | 320 |
| Internal Depth (mm) | 245 | 245 | 245 | 245 | 245 |
| Internal Height (mm) | 550 | 550 | 550 | 550 | 550 |
| BASE CABINET OPTIONS | | | | | |
| Model Number | - | - | - | - | - |
| Width (mm) | - | - | - | - | - |
| Depth (mm) | - | - | - | - | - |
| Height (mm) | - | - | - | - | - |
| POWER REQUIREMENTS | | | | | |
| Hertz | 50 | 50 | 50 | 50 | 50 |
| Volts | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 |
| MAX POWER CONSUMPTION | | | | | |
| Cold & Ambient (W) | 95 | 95 | 95 | 95 | 95 |
| Cold & Hot (W) | - | 545 | - | 545 | - |
| COLD TEMPERATURE | | | | | |
| Min °C | 4 | 4 | 2 | 2 | 2 |
| Max °C | 11 | 11 | 11 | 11 | 11 |
| HOT TEMPERATURE | | | | | |
| Max °C | - | 90 | - | 90 | - |
| DISPENSE LEVEL | | | | | |
| Height (mm) | 210 | 210 | 210 | 210 | 210 |
| THROUGHPUT LITRES PER HOUR | | | | | |
| Cold at 7°C | 12 | 12 | 18 | 18 | 18 |
| Hot at 87 °C | - | 6 | - | 6 | - |

KEY ● Direct Chill ● Cold ○ Sparkling ● Ambient ● Hot